

# HW193DP

# HANNING



## LCD Panel

<b>Display size</b>	19" (48,26 cm) WIDE
<b>Panel Type</b>	Active Matrix TFT
<b>Brightness</b>	300 cd/m <sup>2</sup> (typ.)
<b>Contrast ratio</b>	700:1 (typ.)
<b>Pixel pitch</b>	0.283(H)*0.283(V) mm
<b>Resolution (H x V)</b>	WXGA+ 1440 x 900
<b>Response time</b>	5 ms (typ.)
<b>View angles LR,UD</b>	H/V 150°/135°
<b>Display colors</b>	16.2M Colors
<b>Color</b>	9300K, 6500K, User Mode
<b>Display Surface</b>	Anti-Glare

## Input

<b>Input 1</b>	VGA Analog x1, PC Audio x1
<b>Input 2</b>	DVI

## Output

<b>Output 1</b>	
<b>Output 2</b>	
<b>Headphone</b>	

## Power

<b>Speakers</b>	1W x 2
<b>Supply</b>	AC 100~240V, 50~60Hz
<b>Consumption</b>	55 W

## Operating Condition

<b>Temperature</b>	5 ~ 35°C
<b>Humidity</b>	10 ~ 85%

## Physical

<b>Dimension (W*D*H)</b>	444 x 396 x 199
<b>Packing dimension (W*D*H)</b>	520 x 148 x 412 mm
<b>Net weight</b>	

<b>Gross weight</b>	
<b>Tilt</b>	0°~ 20°

## Controls

<b>Kensington Lock</b>	✓
<b>VESA mounting</b>	VESA Standard, 100mm
<b>Front control</b>	Auto, Vol(-), Power/LED, Vol(+), Menu

## Certification

<b>On screen display</b>	EN,TC,DE,FR,ES,IT,PT,NL,SC,JS,KR
<b>Safety</b>	CE,FCC,BSMI,C-Tick, VCCI, CB, UL/CUL, TUV/Bur-Mark,CCC
<b>Emission</b>	TCO03

## Extras 1

## Extras 2

## Extras 3

## Accessories

<b>Power saving</b>	EPA Energy Star
---------------------	-----------------

powercord, VGA cable, audio cable, users manual (CD), quickstart guide (paper), warranty card

ENG

Specifications are subject to change without notice. Error accepted.

HANNspree Europe GmbH  
Siemensring 66  
47877 Willich  
GERMANY  
Tel: +49 (0)2154/95 323-0  
Fax: +49 (0)2154/95 323-123  
<http://www.hannsg.com>  
[info.europe@hannspree.com](mailto:info.europe@hannspree.com)

GO BEYOND